

# Technical Bulletin – Sealants & Adhesives

## ABOUT THIS BULLETIN

- When installing F-WAVE® REVIA® Roofing Shingles, only use Sealants and Adhesives that have been tested and approved by F-WAVE for use with F-WAVE® REVIA® Roofing Shingles.
- A list of F-WAVE approved Sealants and Adhesives is given in the latest version of the installation manuals available at [fwave roofing.com/resources](http://fwave roofing.com/resources), and also in the **APPROVED SEALANTS & ADHESIVES** section.

## APPROVED SEALANTS & ADHESIVES

- The following Sealants & Adhesives **ARE APPROVED** for use when installing F-WAVE® REVIA® Roofing Shingles or F-WAVE® REVIA® **XTM** Roofing Shingles. See **Table 1**.
- Sealants and adhesives must be applied as outlined in F-WAVE Installation Manuals and according to the sealant/adhesive manufacturers' application instructions including adhering to minimum acceptable installation temperatures and conditions.

MANUFACTURER	PRODUCT NAME
NPC Sealants	#900 Solar Seal®
R.M. Lucas Co.	#6600 Universal™ Terpolymer Sealant
OSI®	QUAD® Sealant
Mule-Hide Products	SEBS 1 Multipurpose Sealant

**TABLE 1 - Approved Sealants & Adhesives**

## PROHIBITED SEALANTS & ADHESIVES

- Use of any other Sealant or Adhesive that has not been tested and approved for use, **will void the F-WAVE WeatherForce® Advantage Standard Product Limited Warranty.**
- This includes, but is not limited to, the following sealants/adhesives which are **NOT APPROVED** for use when installing F-WAVE® REVIA® Roofing Shingles or F-WAVE® REVIA® **XTM** Roofing Shingles and should **NOT** be used at any time. See **Table 2**.

MANUFACTURER	PRODUCT NAME
Mule-Hide Products ( <i>Joint &amp; Termination Sealant</i> )	JTS 1® ( <i>see Mule-Hide SEBS 1, above</i> )
OSI® ( <i>Window, Door &amp; Siding Sealant</i> )	QUAD® MAX ( <i>see OSI® QUAD®, above</i> )

**TABLE 2 - Specifically Prohibited Sealants & Adhesives**

## NOTES

- Review the sealant/adhesive manufacturers' Safety Data Sheets (SDS) and Installation & Use recommendations, particularly regarding weather conditions. Additional information may be found in the NRCA Roofing Manual: Steep-Slope Roof Systems.

*Installers should consult the most recent F-WAVE Installation Manuals at [fwave roofing.com/resources](http://fwave roofing.com/resources) to determine all recommended installation requirements. For additional support or questions, visit [fwave roofing.com](http://fwave roofing.com) or call F-WAVE Technical Support at **1-888-GO-FWAVE** (1-888-463-9283). All product names, logos, and brands are property of F-WAVE, LLC or their respective owners. All company, product and service names used are for identification purposes only. Use of these names, logos, and brands does not imply endorsement.*