

INTERLOCKING ROOFING SHINGLES

Designed with integrated front edge and nail-line hooks that are adjustable, **XTM™** simply and mechanically interlocks together for **EXTREME** wind and hail performance. **XTM™** is the first **FM 4475 Very Severe Hail** rated shingle with warranted coverage and has a **180 mph wind warranty** with nails and an unlimited wind warranty with screws. Crews can now also install year-round without compromise, as **XTM™** has **no minimum temperature installation restrictions**.



FM 4475 Very Severe Hail and
 UL2218 Class 4 hail impact rated
 (with warranted damage coverage)



130 mph 1 ¼" smooth shank nails
 180 mph 1 ½" ring shank nails
 Unlimited 1 ½" raised head screws



Interlocking with adjustability



Class A fire rated
 (see installation instructions)



Tough interlocking shingles for
 lasting durability



Ultra-dimensional
 premium appearance



Resistant to cracking and fading
 (with warranted coverage)



No asphalt to become
 brittle



No granules to fall off



No minimum installation
 temperature

10

SHINGLES
 PER BUNDLE

60

SHINGLES
 PER SQUARE

6.1"

EXPOSURE

6

NAILS PER
 SHINGLE



EXCLUSIVE 5-YEAR HAIL COVERAGE



Charcoal Blend



Harvest Blend



Birchwood Blend

Charcoal Blend



Harvest Blend



Birchwood Blend

