

INTERLOCKING ROOFING SHINGLES

Designed with integrated front edge and nail-line hooks that are adjustable, **XTM™** simply and mechanically interlocks together for **EXTREME** wind and hail performance. **XTM™** is the first **FM 4475 Very Severe Hail** rated shingle with warranted coverage and has a **180 mph wind warranty** with nails and an unlimited wind warranty with screws. Crews can now also install year-round without compromise, as **XTM™** has **no minimum temperature installation restrictions**.



FM 4475 Very Severe Hail and
UL2218 Class 4 hail impact rated
(with warranted damage coverage)



130 mph 1 ¼" smooth shank nails
180 mph 1 ½" ring shank nails
Unlimited 1 ½" raised head screws



Interlocking with adjustability



Class A fire rated
(see installation instructions)



Tough interlocking shingles for
lasting durability



Ultra-dimensional
premium appearance



Resistant to cracking and fading
(with warranted coverage)



No asphalt to become
brittle



No granules to fall off



No minimum installation
temperature

10

SHINGLES
PER BUNDLE

60

SHINGLES
PER SQUARE

6.1"

EXPOSURE

6

NAILS PER
SHINGLE



Castlewood Brown



Mountain Cedar



Lakeshore Gray



Mountain Cedar



Castlewood Brown



Lakeshore Gray